

■銅線用裸圧着端子 / NON INSULATED TERMINAL

PART No.	d ₂	B	L	F	E	D	d ₁	t	pcs./Reel	
1.25	1.25-3TR	3.2	5.5	12.0	4.75	4.5	3.4	1.7	0.75	
	1.25-3.5TR	3.7	6.5	13.6	5.85					
	1.25-FS3TR	3.2	5.8	13.25	5.85					
	1.25-4TR	4.3	8.0	15.8	7.3					
	1.25-F4TR	4.3	6.5	13.6	5.85					
2	1.25-5TR	5.3	8.0	15.8	7.3	5.0	4.2	2.3	0.8	
	2-FS3TR	3.2	5.8	15.2	7.3					
	2-3.5TR	3.7	6.6	15.6	7.3					
	2-FS3.5TR	3.7	5.8	15.2	7.3					
	2-4TR	4.3	8.5	16.5	7.25					
1.25	2-F4TR	4.3	6.6	15.6	7.3	4.5	3.4	1.7	0.75	
	2-5TR	5.3	9.5	17.2	7.45					
	1.25-YAS3TR	3.3	5.8	15.0	5.8					
	1.25-YAS3.5TR	3.7	6.4	15.0	6.0					
	1.25-YAS4TR	4.3	6.8	15.0	5.8					
2	2-YAS3TR	3.3	5.8	16.0	6.5	5.0	4.2	2.3	0.8	
	2-YAS3.5TR	3.7	6.4	16.0	6.5					
	2-YAS4TR	4.3	6.8	16.0	6.5					

・太字はJIS規格品です

■銅線用絶縁被覆付圧着端子(V型) / INSULATED TERMINAL(V TYPE)

PART No.	Color	d ₂	B	L	F	D	ℓ	t	pcs./Reel		
1.25	RED	V1.25-3TR (RAA1.25-3)	3.2	5.5	17.0	4.75	3.2	9.5	0.8	1,000	
		V1.25-3.5TR (RAA1.25-3.5)	3.7	6.5	18.6	5.85					
		V1.25-FS3TR	3.2	5.8	18.25	5.85					
		V1.25-4TR (RAA1.25-4)	4.3	8.0	20.8	7.3					
		V1.25-F4TR	4.3	6.5	18.6	5.85					
2	BLUE	V1.25-5TR (RAA1.25-5)	5.3	8.0	20.8	7.3	3.8	9.5	0.8		
		V2-FS3TR	3.2	5.8	19.7	7.3					
		V2-3.5TR (RAA2-3.5)	3.7	6.6	20.1	7.3					
		V2-FS3.5TR	3.7	5.8	19.7	7.3					
		V2-4TR (RAA2-4)	4.3	8.5	21.0	7.25					
1.25	RED	V2-F4TR	4.3	6.6	20.1	7.3	3.2	9.5	0.8		
		V2-5TR (RAA2-5)	5.3	9.5	21.7	7.45					
		V1.25-YAS3TR	3.3	5.8	20.0	5.8					
		V1.25-YAS3.5TR	3.7	6.4	20.0	6.0					
		V1.25-YAS4TR	4.3	6.8	20.0	5.8					
2	BLUE	V2-YAS3TR	3.3	5.8	20.5	6.5	3.8	9.5	0.8		
		V2-YAS3.5TR	3.7	6.4	20.5	6.5					
		V2-YAS4TR	4.3	6.8	20.5	6.5					

・()はJIS型番です

■銅線用絶縁被覆付圧着端子(BT型) / INSULATED TERMINAL(BT TYPE)

PART No.	Color	d ₂	B	L	F	D	ℓ	t	pcs./Reel		
1.25	RED	BT1.25-3TR (RBA1.25-3)	3.2	5.5	17.0	4.75	3.8	9.5	0.8	1,000	
		BT1.25-3.5TR (RBA1.25-3.5)	3.7	6.5	18.6	5.85					
		BT1.25-FS3TR	3.2	5.8	18.25	5.85					
		BT1.25-4TR (RBA1.25-4)	4.3	8.0	20.8	7.3					
		BT1.25-F4TR	4.3	6.5	18.6	5.85					
2	BLUE	BT1.25-5TR (RBA1.25-5)	5.3	8.0	20.8	7.3	4.5	9.5	0.8		
		BT2-FS3TR	3.2	5.8	19.7	7.3					
		BT2-3.5TR (RBA2-3.5)	3.7	6.6	20.1	7.3					
		BT2-FS3.5TR	3.7	5.8	19.7	7.3					
		BT2-4TR (RBA2-4)	4.3	8.5	21.0	7.25					
1.25	RED	BT2-F4TR	4.3	6.6	20.1	7.3	3.8	9.5	0.8		
		BT2-5TR (RBA2-5)	5.3	9.5	21.7	7.45					
		BT1.25-YAS3TR	3.3	5.8	20.0	5.8					
		BT1.25-YAS3.5TR	3.7	6.4	20.0	6.0					
		BT1.25-YAS4TR	4.3	6.8	20.0	5.8					
2	BLUE	BT2-YAS3TR	3.3	5.8	20.5	6.5	3.8	9.5	0.8		
		BT2-YAS3.5TR	3.7	6.4	20.5	6.5					
		BT2-YAS4TR	4.3	6.8	20.5	6.5					

・()はJIS型番です